

SS32G~SS320G

ROHS

Surface Mount Schottky Barrier Rectifier

Features


- ◆ Metal silicon junction, majority carrier conduction
- ◆ For surface mounted applications
- ◆ Low power loss, high efficiency
- ◆ High forward surge current capability
- ◆ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

Mechanical Data

- ◆ Case: SMA
- ◆ Quantity Per Reel : 2,000pcs
- ◆ Approx. Weight : 60mg / 0.0021oz
- ◆ Terminals: Solderable per MIL-STD-750, Method 2026



www.unsemi.com.tw



Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

| Parameter | | Symbol | SS32G | SS34G | SS36G | SS38G | SS310G | SS312G | SS315G | SS320G | Units |
|--|---------|--------|------------|-------|-------|-------|--------|--------|--------|--------|-------|
| Maximum Repetitive Peak Reverse Voltage | | VRRM | 20 | 40 | 60 | 80 | 100 | 120 | 150 | 200 | V |
| Maximum RMS voltage | | VRMS | 14 | 28 | 42 | 56 | 70 | 84 | 105 | 140 | V |
| Maximum DC Blocking Voltage | | VDC | 20 | 40 | 60 | 80 | 100 | 120 | 150 | 200 | V |
| Maximum Average Forward Rectified Current | | IF(AV) | 3.0 | | | | | | | | A |
| Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method) | | IFSM | 80 | | | | | | | | A |
| Max Instantaneous Forward Voltage at 3A | | VF | 0.55 | 0.70 | | 0.85 | | 0.95 | | V | |
| Maximum DC Reverse Current at Rated DC Reverse Voltage | Ta=25℃ | IR | 0.5 | | | 0.3 | | | | mA | |
| | Ta=100℃ | IR | 5.0 | | | 3.0 | | | | | |
| Typical Junction Capacitance ⁽¹⁾ | | Cj | 450 | | | 400 | | | | pF | |
| Typical Thermal Resistance ⁽²⁾ | | RθJA | 70 | | | | | | | | ℃/W |
| Operating Junction Temperature Range | | TJ | -55 ~ +150 | | | | | | | | ℃ |
| Storage Temperature Range | | Tstg | -55 ~ +150 | | | | | | | | ℃ |

Note: (1) Measured at 1 MHz and applied reverse voltage of 4VDC.

(2) P.C.B. mounted with 2.0" X 2.0" (5 X 5cm) copper pad areas.

Electrical Characteristics Curves

Fig.1 Forward Current Derating Curve




Fig. 2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig. 4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current






Fig. 6 Typical Transient Thermal Impedance



Package Outline & Dimensions



| Dimensions | Inches | | Millimeters | |
|------------|--------|-------|-------------|-------|
| | Min. | Max. | Min. | Max. |
| A | 0.049 | 0.064 | 1.230 | 1.630 |
| B | 0.162 | 0.179 | 4.10 | 4.550 |
| C | 0.099 | 0.109 | 2.510 | 2.760 |
| D | 0.077 | 0.089 | 1.960 | 2.260 |
| E | 0.030 | 0.060 | 0.750 | 1.510 |
| F | - | 0.008 | - | 0.203 |
| G | 0.192 | 0.206 | 4.87 | 5.220 |
| H | 0.006 | 0.012 | 0.152 | 0.305 |
| I | 0.070 | - | 1.800 | - |
| J | 0.082 | - | 2.100 | - |
| K | - | 0.090 | - | 2.300 |
| L | 0.082 | - | 2.100 | - |

Marking

| Type Number | SS32G | SS34G | SS36G | SS38G | SS310G | SS312G | SS315G | SS320G |
|-------------|-------|-------|-------|-------|--------|--------|--------|--------|
| Making | SS32 | SS34 | SS36 | SS38 | SS310 | SS312 | SS315 | SS320 |

Disclaimer

UNSEMI RESERVES THE RIGHT TO MAKE CHANGE ON OUR PRODUCTS , PRODUCTS SPECIFICATION AND DATA WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

UN SEMICONDUCTOR LIMITED its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "UNSEMI") does not give any representations or warranties for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

In no event shall UNSEMI be liable for any indirect, incidental, punitive, special or consequential damages (including any and all implied warranties, warranties of fitness for particular purpose, non-infringement and merchantability.) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Statements regarding the suitability of products for certain types of applications are based on UNSEMI knowledge of typical requirements that are often placed on UNSEMI products in generic applications. Such statements are not binding, statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify UNSEMI's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Unless otherwise agreed in writing, UNSEMI product is not designed, authorized or warranted to be suitable for use in medical life-saving, or life-sustaining application , nor in applications where failure or malfunction of a UNSEMI product can reasonably be expected to result in personal injury, death or severe property or environmental damage. UNSEMI and its suppliers accept no liability for inclusion or use of UNSEMI products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

All referenced brands, product names, service names and trademarks are the property of their respective owners.