

US1A~US1M

Surface Mount Fast Recovery Rectifiers

ROHS

Features


- ◆ For surface mounted applications
- ◆ Low profile package
- ◆ Glass passivated chip junction
- ◆ Easy to pick and place
- ◆ High efficiency
- ◆ Lead free in comply with EU RoHS 2011/65/EU directives

Mechanical Data

- ◆ Case: SMA
- ◆ Quantity Per Reel : 2,000pcs
- ◆ Approx. Weight: 60mg / 0.0021oz
- ◆ Terminals: Solderable per MIL-STD-750, Method 2026



www.unsemi.com.tw



Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter		Symbol	US1A	US1B	US1D	US1G	US1J	US1K	US1M	Units
Maximum Repetitive Peak Reverse Voltage		VRRM	50	100	200	400	600	800	1000	V
Maximum RMS Voltage		VRMS	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage		VDC	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at Tc=125°C		IF(AV)	1.0							A
Peak Forward Surge Current 8.3ms Single Half Sine Wave Superimposed on Rated Load		IFSM	30							A
Maximum Forward Voltage at 1A		VF	1.0			1.3	1.65			V
Maximum DC Reverse Current at Rated DC Blocking Voltage	Ta=25°C	IR	5							μA
	Ta=125°C	IR	100							μA
Maximum Reverse Recovery Time ⁽¹⁾		trr	50				75			nS
Typical Thermal Resistance ⁽²⁾		RθJA	75							°C/W
Operating and Storage Temperature Range		TJ,Tstg	-55 ~ +150							°C

Note:(1) Measured with IF=0.5A, IR=1A, Irr=0.25A

(2) P.C.B. mounted with 2.0" X 2.0" (5 X 5cm) copper pad areas.

Electrical Characteristics Curves

Fig.1 Forward Current Derating Curve




Fig. 2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic






Fig.4 Maximum Non-Repetitive Peak Forward Surge Current



Package Outline & Dimensions (Units: mm / in)



Dimensions	Inches		Millimeters	
	Min.	Max.	Min.	Max.
A	0.049	0.064	1.230	1.630
B	0.162	0.179	4.10	4.550
C	0.099	0.109	2.510	2.760
D	0.077	0.089	1.960	2.260
E	0.030	0.060	0.750	1.510
F	-	0.008	-	0.203
G	0.192	0.206	4.87	5.220
H	0.006	0.012	0.152	0.305
I	0.070	-	1.800	-
J	0.082	-	2.100	-
K	-	0.090	-	2.300
L	0.082	-	2.100	-

Marking

Type Number	US1A	US1B	US1D	US1G	US1J	US1K	US1M
Making	US1A	US1B	US1D	US1G	US1J	US1K	US1M

Disclaimer

UNSEMI RESERVES THE RIGHT TO MAKE CHANGE ON OUR PRODUCTS , PRODUCTS SPECIFICATION AND DATA WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

UN SEMICONDUCTOR LIMITED its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "UNSEMI") does not give any representations or warranties for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

In no event shall UNSEMI be liable for any indirect, incidental, punitive, special or consequential damages (including any and all implied warranties, warranties of fitness for particular purpose, non-infringement and merchantability.) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Statements regarding the suitability of products for certain types of applications are based on UNSEMI knowledge of typical requirements that are often placed on UNSEMI products in generic applications. Such statements are not binding, statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify UNSEMI's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Unless otherwise agreed in writing, UNSEMI product is not designed, authorized or warranted to be suitable for use in medical life-saving, or life-sustaining application , nor in applications where failure or malfunction of a UNSEMI product can reasonably be expected to result in personal injury, death or severe property or environmental damage. UNSEMI and its suppliers accept no liability for inclusion or use of UNSEMI products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

All referenced brands, product names, service names and trademarks are the property of their respective owners.